SMART™

SIP COMMUNICATIONS SIMPLIFIED

SIP VOIP PHONE

MODEL (WMHS-IP)

MODEL (WMHS-IP-POE)



VOIP SIP PHONE

As a SIP phone can be connected to any standard IP PABX, available in dial keypad and non-dial versions.

SMART DESIGN

Housed in IP 65 resistant, 16 SWG Powder Coated steel body and manufactured to high standard, these telephones offer increased resistance to vandalism, and ensure that the primary function of communication is maintained at all times.

PROTOCOLS / STANDARDS

STANDARD SIP

PROTOCOLS ETWORK INTERFACE

10/100 Mbps RJ 45 Ethernet port.

VOICE CODE

Support for G.711µ/a, G.722 (wide-band), G.723, G.726-32, G.729 A/B, iLBC, in-Band and out-of-band DTMF (In audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJB, AGC

.

SMART CHOICE

- Simple Installation.
- Simple Operation.
- Relay contact for external Ringer flasher.
- Windows application for extension configuration.

SPECIFICATIONS

Power Supply

Universal Power Supply:- Input 100-220V AC.
POE : - POE (Power over Ethernet) IEEE802.3af. (Model - WMHS-IP-POE)

Temperature and Humidity

Operation:-10°C to +60°C, Humidity: 10%
To 90% Non-condensing

DISPLAY

132 x 48 (2.95'') backlit graphical LCD

Mechanical

Hook switch (magnetic reed) life	>1 000 000 operations.
Body construction	**16 SWG Powder Coated Steel Body**
Dimensions	360X160X180 mm.
Net weight	2 kgs.
Handset material	High impact ABS.
Microphone	Noise reducing dynamic.
Standard mounting	Vertical wall.
Handset cord	Stainless steel.
Weather proof	IP 65 Resistant

"(Specifications and description subjected to change without prior notice)"

MADE IN INDIA

CABLES & WIRELESS CO.

FF 75 RAJAT ARCADE, MIDC T-POINT,

AMRAWATI ROAD, WADI,

NAGPUR -440023

PHONE:-07104-321913, 07104-224381 Fax:- 07104-224381

Website:- www.cnwcom.in. E-mail: - cnwcom@gmail.com.

Cell: - 098226 95746, 09822941190.